



**STAINLESS STEEL PIPE**

**WELDED / SEAMLESS PIPE**

Manufactured to - ASTM A-312

OUTSIDE DIAMETER NB	mm	SCHEDULE 10 WELDED PIPE			
		WALL THICKNESS	WEIGHT	304L	316L
		mm	kg/m		
1/4"	13.70	1.65	0.49	•	•
3/8"	17.50	1.65	0.63	•	•
1/2"	21.34	2.11	1.00	•	•
3/4"	36.67	2.11	1.28	•	•
1"	33.53	2.77	2.09	•	•
1 1/4"	42.16	2.77	2.70	•	•
1 1/2"	48.26	2.77	3.10	•	•
2"	60.45	2.77	3.30	•	•
2 1/2"	73.15	3.05	5.26	•	•
3"	88.90	3.05	6.45	•	•
4"	114.30	3.05	8.35	•	•
5"	141.30	3.40	11.56	•	•
6"	168.15	3.40	13.82	•	•
8"	218.95	3.76	19.93	•	•
10"	273.05	4.19	27.82	•	•
12"	323.85	4.57	35.95	•	•
14"	355.60	4.77	42.20		•
16"	406.40	4.77	48.30		•
18"	457.20	4.77	54.41		•
20"	508.00	5.54	66.80		•

SCHEDULE 40 WELDED PIPE			
WALL THICKNESS	WEIGHT	304L	316L
mm	kg/m		
2.24	0.63	•	•
2.31	0.84	•	•
2.77	1.27	•	•
2.87	1.68	•	•
3.38	2.49	•	•
3.56	3.38	•	•
3.68	4.04	•	•
3.91	5.44	•	•
5.16	8.62	•	•
5.49	11.27	•	•
6.02	16.05	•	•
6.55	21.75	•	•
7.11	28.22	•	•
8.18	43.2	•	•
9.27	61.05		•
10.3	74.81		•
11.1	94		•
12.7	123		•
14.2	155.8		•
15.06	183		•

OUTSIDE DIAMETER NB	mm	SCHEDULE 10 WELDED PIPE			
		WALL THICKNESS	WEIGHT	304L	316L
		mm	kg/m		
1/4"	13.70				
3/8"	17.50				
1/2"	21.34	3.73	1.64		•
3/4"	36.67	3.91	2.22		•
1"	33.53	4.55	3.28		•
1 1/4"	42.16	4.85	4.52		•
1 1/2"	48.26	5.08	5.48		•
2"	60.45	5.54	7.48		•
2 1/2"	73.15	7.01	11.41		•
3"	88.90	7.62	15.47		•
4"	114.30	8.56	22.6		•
5"	141.30	10.97	42.6		•
6"	168.15				
8"	218.95				
10"	273.05				
12"	323.85				
14"	355.60				
16"	406.40				
18"	457.20				
20"	508.00				